

SPECIFICATION

Quality		: COSMOS
Product definition		: cut pile
Gauge		: 5/32
No. of tufts	ISO 1763	: $\pm 112950 /m^2$
Pile fibre		: 100% Polypropylene
Pile weight	ISO 8543	: $890 \text{ gr}/m^2 \pm 5\%$
Pile height	ISO 1766	: $7.9 \text{ mm} \pm 5\%$
Primary backing		: PA/PES non-woven - Colback
Tile backing		: Polyflex
Total thickness	ISO 1765	: $9.9 \text{ mm} \pm 5\%$
Total weight	ISO 8543	: $4452 \text{ gr}/m^2 \pm 7,5\%$
Tile size		: $50 \times 50 \text{ cm} (\pm 19.7'' \times 19.7'')$
Tiles per box		: 20

PERFORMANCE

Use classification	method en 1307	: 23
Castor chair test	EN 985	:
Luxery/Comfort	EN 1307	: class 5

ELECTROSTATIC PROPERTIES

Static loading		: anti-static
----------------	--	---------------

FLAME PROPERTIES

Reaction to fire	EN ISO 11925-2	
	EN ISO 9239-1	: $B_{fl} - s1$



GENERAL

Recommended maintenance:
Pile direction:

Best results are obtained when cleaned with a dry shampoo method.
Directional arrows are printed on the back of each tile.
Best results are obtained when laid checkerboard.

Laying instructions:

Tiles require no underlay, nailing, gluing or sewing and may be laid loose on a flat, dry, non-slippery floor. When tiles are laid on parquet, vinyl or in open areas larger than 30 m^2 it is advisable to use double sided adhesive tape on every 8th row or a tackifier.

COLOURS

2176 Mid. Grey	2240 Green
	2114 Purple

2220 Red	2376 Grey
-------------	--------------

2272 Beige	2276 GreyBrown
2269 L. Beige	

2180 Dark. Blue	2283 Petrol Blue
	Polyflex Backing