

SPECIFICATION

Quality		: AMADEUS
Product definition		: Cut pile
Gauge		: 5/32"
No. of tufts	ISO 1763	: $\pm 73080/m^2 -7.5\% +10\%$
Pile fibre		: 100% PES (polyester)
Pile weight	ISO 8543	: $1650 \text{ gr}/m^2$
Pile height	ISO 1766	: $\pm 11 \text{ mm}$
Tile backing		: Polyflex with glass fibre scrim
Total thickness	ISO 1765	: $\pm 13 \text{ mm} \pm 5\%$
Total weight	ISO 8543	: $5000 \text{ gr}/m^2 \pm 10\%$
Tile size		: $50 \times 50 \text{ cm} (\pm 19.7'' \times 19.7'')$
Tiles per box		: 12

PERFORMANCE

Use classification		: 23, heavy domestic use
Luxury/Comfort	EN 1307	: classe 5

FLAME PROPERTIES

Reaction to fire	EN ISO 11925-2 EN ISO 9239-1	: B _{f1} -s1
------------------	---------------------------------	-----------------------



COLOUR FASTNESS PROPERTIES

Light	ISO 105 B02	: > 5
Rubbing, dry	ISO 105 X12	: > 4
Rubbing, wet	ISO 105 X12	: > 4
Water	ISO 105 E01	: > 4

GENERAL

Recommended maintenance:
Pile direction:

Best results are obtained when cleaned with a dry shampoo method.
Directional arrows are printed on the back of each tile.
Best results are obtained when laid checkerboard.

Laying instructions:

Tiles require no underlay, nailing, gluing or sewing and may be laid loose on a flat, dry, non-slippery floor. When tiles are laid on parquet, vinyl or in open areas larger than 30 m² it is advisable to use double sided adhesive tape on every 8th row or a tackifier.

COLOURS

78 Antra	11 Pink	92 Grey Brown	74 L. Grey
75 Grey	70 White	72 Beige	76 Grey Blue