

# HIMALAYA TILES

## DOP 1020/126903

Fabrieksmethode Mode de fabrication Herstellungsverfahren Manufacturing process	Getuft, 1/10" lussenpool Tufté, 1/10" velours bouclé Getuftet, 1/10" Schlinge Tufted, 1/10" loop pile					
Samenstelling van de pool Composition du velours Nutzschicht Pile composition	80 % zuivere scheerwol – 19,7% PA – 0.3% Bekinox 80 % laine vierge – 19,7% PA – 0.3% Bekinox 80 % reine Schurwolle – 19,7% PA – 0.3% Bekinox 80 % pure new wool – 19,7% PA – 0.3% Bekinox					
Tuftdoek Support Trägergewebe Primary backing	100 % PES					
Rug Dossier Rücken Secondary backing	Bitumen, covered with PES-fleece		1	Wit Blanc Weiss White	15	Hout Bois Holz Wood
Poolhoogte Hauteur du velours Polhöhe Pile height	3 mm		35	Zilvergrijs Gris Argent Silbergrau Silver Grey	5	Beige Beige Beige Beige
Totale hoogte Hauteur totale Gesamthöhe Total height	7,5 mm		50	Antraciet Antracite Anthrazit Antracite	40	Middengrijs Gris Moyen Mittelgrau Mid Grey
Aantal noppen Nombre de points Noppenzahl Tuft density	188990/m <sup>2</sup>		70	Blauw Bleu Blau Blue	25	Muisgrijs Gris Souris Mausgrau Mouse Grey
Poolgewicht Poids du velours Polgewicht Pile weight	1150 g/m <sup>2</sup>					
Totaal gewicht Poids total Gesamtgewicht Total weight	4620 g/m <sup>2</sup>					
Warmte isolatie Résistance à la conductibilité de chaleur Wärmedurchlasswiderstand Resistance of heat conduction	ISO 8302 0,15 m <sup>2</sup> K/W (theoretisch)	Tog rating 1.5				
Impact noise rating DLw ISO 140-8 Permanent antistatic ISO 6356 Dimensions Packing	25 dB <2 kV 50cmx50cm, dimensional stability <0.20 % Box : 5m <sup>2</sup> ; pallet=20 boxes					

Lay on a flat rigid and sound surface with special supporting primer for removable weighted tiles. Start in the middle of the room at a distance of several tiles from the door. Directional arrows are printed on the back of the tile for orientation. We advise to install as a checkboard.

We reserve the right to modify the characteristics of this product for quality improvement.

Also available as broadloom carpet in 4 & 5m width in cut length service.



GARANTIE  
WAARBORG  
**5**  
GARANTEE