

WOOLEN TILES

Candy Stripe

Sintra

Fabrikatiemethode Mode de fabrication Herstellungsverfahren Manufacturing process	Getuft, 1/10" lussenpool Tufté, 1/10" velours bouclé Getuftet, 1/10" Schlinge Tufted, 1/10" loop pile				
Samenstelling van de pool Composition du velours Nutzschicht Pile composition	100 % zuivere scheerwol 100 % laine vierge 100 % reine Schurwolle 100 % pure new wool				
Tuftdoek Support Trärgewebe Primary backing	100 % PES				
Rug Dossier Rücken Secondary backing	10000	Dune Colours	Bitumen, covered with PES-fleece	26070	Creme
	20000	Wood Colours		26630	Praliné
Poolhoogte Hauteur du velours Polhöhe Pile height	30000	Stone Colours	5 mm	26150	Mid Beige
	40000	Harvest Colours		26650	Mousse Gray
Totale hoogte Hauteur totale Gesamthöhe Total height	70000	Vanille Colours	7,5 mm	26610	Wood
	11000	Earth Colours		26660	Anthracite
Aantal noppen Nombre de points Noppenzahl Tuft density	154 000/m²				
Poolgewicht Poids du velours Polgewicht Pile weight	1 020 g/m²				
Totaal gewicht Poids total Gesamtgewicht Total weight	4 250 g/m²				
Warmte isolatie Résistance à la conductibilité de chaleur Wärmedurchlasswiderstand Resistance of heat conduction	DIN 52612 0,15 m² K/W				
Impact noise rating DLw ISO 140-8 Permanent antistatie ISO 6356 Dimensions Packing	25 dB <2 kV 50 cm x 50 cm, dimensional stability <0.20 % Box: 5m² ; pallet = 20 boxes				

Lay on a flat rigid and sound surface with special supporting primer for removable weighted tiles. Start in the middle of the room at a distance of several tiles from the door. Directional arrows are printed on the back of the tile for orientation. We advise to install as a checkboard.

We reserve the right to modify the characteristics of this product for quality improvement.

Also available as broadloom carpet in 4 & 5 m width in cut length service and rolls.

